

→

NPDL- C002 0 1

- 1 24V DC
- 2 220V AC

→

:
18V DC~32V DC (24V DC)
85V AC~265V AC (120V DC~360V DC)

(1 2):

0~1A; 0~2.5A; 0~5A; 0~10A

(7 8 9):

4mA~20mA
0(4)mA~20mA; 0mA~10mA
1~5V; 0~5V; 0~10V

:

$$R_t \leq [(U-3)/0.024] \Omega; U$$

0(4)mA~20mA: $\leq 550\Omega$; 0mA~10mA: $\leq 1.1k\Omega$

0(1)V~5V: 1M Ω ; 0V~10V: 2M Ω

: 0.2%F.S. (0~120%)

: < 16mV_{rms} (250 Ω)

: 0.01%F.S./ $^{\circ}C$

: 40Hz~400Hz

: < 330ms

: 2

: EMC IEC 61326-3-1

(1mA 1):

1500 V AC (/ /)

:

-20 $^{\circ}C$ ~+60 $^{\circ}C$

10%RH~90%RH(40 $^{\circ}C$)

80kPa~106kPa

-40 $^{\circ}C$ ~+80 $^{\circ}C$

:

24V DC供电 < 1W

220V AC供电 < 2W

0	
1	4mA~20mA
2	1V~5V
3	0mA~10mA
4	0V~5V
5	0V~10V
6	0mA~20mA
7	

○

○

→

× × : 17.8mm×110mm×117mm

→

○

DIN IEC 60715 35mm

○

Nanjing New Power Electric Co., Ltd.

→

○ PWR: ()

→

○

○

○

○

○

○ IEC/EN 60664-1 2